



STRENGTHS

+ Easy maintenance

MEDIVA's separate compartment for medical gas provide quick and easy access for installation and maintenance. The bed head unit can be installed quickly in just three steps, saving time and manpower.

+ Design & Ergonomics

MEDIVA's electrical devices are ideally positioned, with easy access for patients and care staff. The bed head unit has smooth surfaces, making it easy to clean.


+ Personalisation

Gas casing are available in seven colours, to match with the decor of normal care rooms.




TECHNICAL FEATURES

Front view



Cross-section




- ① General and Night light compartment
- ② Reading lighting compartment
- ③ Low voltage compartment
- ④ Extra low voltage compartment
- ⑤ Medical gas compartment

Colours

	WHITE RAL 9016	GREY RAL 9006	GREY RAL 7040	ORANGE RAL 2003	BLUE RAL DESIGN 260 80 15	PLUM RAL DESIGN 330 30 35	PINK RAL DESIGN 010 80 20	GREEN RAL DESIGN 110 70 77
Aluminum profile	●	●						
End caps	●	●						
Gas casing	●		●	●	●	●	●	●

Seven panel colours, to match the MEDIVA with the decor of your normal care rooms.




FUNCTIONALITY

The MEDIVA bed head unit is entirely custom made, and provides comfortable, soothing indirect lighting for patients and care teams.

Power supply


MEDIVA is designed to be fed:

- From behind (A), via a cut-out in the bed head unit
- From the ceiling, by a riser (B)
- From the side, through an extra duct (C)



Installation

The MEDIVA is quick and easy to install thanks to its screw-mounting system via the back of the bed head unit.



Electrical equipment integration

The waterjet cutting of the MEDIVA's cover enables exact and customized cutting. It can integrate all forms of outlets. Flush mounting of electrical equipment enables easier cleaning and disinfection of the product.



Medical gas casing

The ABS / PC medical gas casing, available with flap (A) or without flap (B), allow any gas outlet to be installed (e.g.: AFNOR, DIN, BS, etc.).



CONTROLLED LIGHTING

The optics of the MEDIVA allow optimum control of the lighting, favouring the well-being of care teams and patients.

Efficient lighting

The reflectors provide high output and focus the light.

Comfortable lighting


Reading lighting is provided with an anti glare effect diffuser.

Controlled and directed lighting

General lighting includes a diffuser with prism which directs the luminous flux toward the centre of the room.


General lighting

- Clear polycarbonate diffuser opal with anti-UV treatment
- MIRO 20 SILVER® aluminium reflector




Reading lighting

- Opal polycarbonate diffuser with anti-UV treatment
- MIRO 20 SILVER® aluminium reflector



Caring lighting


Caring lighting combines direct (reading) lighting with indirect (general) lighting.



EFFICIENT LIGHTING

Lighting study

- Standard room
- Dimensions of the room: 3 m x 3 m, ceiling clearance 2.5 m
- Reflection coefficients: ceiling 7, walls 5, and floor 3
- Coefficient of depreciation 0.83



	General lighting Virtual general lighting plane of a surface equal to the one of the room, located 0.85 m above the floor (3 m x 3 m for a single room).	Reading lighting Virtual reading plane 0.3 m x 0.3 m inclined at 75° located 1.1 m from the floor and 1 m from the wall where the unit is located.	Caring lighting Virtual examination plane 2 m x 0.9 m located 0.85 m from the floor, centred in width and 0.1 m from the wall.
LED	4 Ft module 	2 Ft module 	General and reading lighting combined
Consumption	42,1 W	20,3 W	62,4 W
Average lighting	133 lx	335 lx	423 lx

Lighting power


Lighting	Power	Types of sources	Color temperature	Luminous Flux	Consumption	System Efficiency	Driver(s)
General lighting	36,7 W (4 Ft)	LED	3000 K 4000 K	5674 lm	42,1 W	135 lm/W	Fixed / 1-10 V / DALI
	45,5 W (5 Ft)	LED	3000 K 4000 K	7093 lm	52,2 W	136 lm/W	Fixed / 1-10 V / DALI
Reading lighting	10,5 W (2 Ft)	LED	3000 K 4000 K	2641 lm	20,3 W	130 lm/W	Fixed / 1-10 V / DALI
Night light	1 x 3,1 W	LED	3000 K	335 lm	4,9 W	68,4 lm/W	Fixed



Norms & certifications

- EN ISO 9001 and EN ISO 13485: Quality management systems
- CE Medical Devices Marking according to 93/42/EEC Directive
- EN ISO 11197: Medical supply units
- EN ISO 7396-1: Medical gas pipeline systems - Part 1
- European rules for caring centers lighting

Bed head units, Wall lighting units, Ceiling pendants, Suspended Beams & Columns,
Special care bed head units, Sealed lightings, Medical gas monitoring & Biomedical Accessories



All specifications herein are provided for information purposes only and may be modified by TLV without notice.(E) - Update (JJ/MM/AA) : 09/04/2019